


Materials

Black-oxide steel
or AISI 303 Stainless steel

Mechanical Spring Plungers

DISCOUNTS

1 - 15	List Price
20-39	-15%
40-59	-20%
60-99	-25%
100+	-30%



PART NUMBER		Main dimensions					Spring press.		Weight g	PRICE EACH 1-15	
							Preload [N~]	Max. load [N~]		Steel	Stainless
Steel	Stainless	d 6g	d1	l ±0.1	l1				Steel	Stainless	
HPCBPM3	HPCBPM3SS	M3	1.5	7	0.4	3	4.5	1	£2.08	£15.57	
HPCBPM4	HPCBPM4SS	M4	2.5	9	0.8	6	14.5	1	£1.58	£4.84	
HPCBPM5	HPCBPM5SS	M5	3.0	12	0.9	8	14	1	£1.58	£4.84	
HPCBPM6	HPCBPM6SS	M6	3.5	14	1.0	11	18	2	£1.58	£4.84	
HPCBPM8	HPCBPM8SS	M8	4.5	16	1.5	18	31	4	£2.12	£6.28	
HPCBPM10	HPCBPM10SS	M10	6.0	19	2.0	24	45	7	£2.25	£7.20	
HPCBPM12	HPCBPM12SS	M12	8.0	22	2.5	26	49	10	£3.71	£8.78	
HPCBPM16	HPCBPM16SS	M16	10.0	24	3.5	41	86	24	£6.38	£8.66	
HPCBPM20	HPCBPM20SS	M20	12.0	30	4.5	56	111	43	£7.36	£16.59	

Threaded body

Black-oxide steel or AISI 303 stainless steel, screwdriver slotted head.

Ball and spring

Hardened steel or stainless steel ball, steel or stainless steel spring with normal end-force.

Working temperature

From -40°C to +170°C.